| | | | | | | | | | | | | | 11 | | | | |
|----------------|-----------------|-----------------|-----|----------|---------------|---------------|-------------------------------|-------------------------------|-----------------|-------------|------------------------|------|-------------|-----------------|--------|-----------------|-----------------|
| ST | anfori | o magn | ETS | | | | | | | | | | | | | 1 1 1 1 1 | |
| ÷. | Ч. | <u>.</u> | ÷. | ÷. | ÷ | ÷. | 1 | : | | `` . | <u>.</u> | | ÷. | 11. | | 1.1 | |
| · · · · | . | | j. | · | | | | | | - | | Su. | 1 11 | \ | Ą | | |
| .:ť | 1 I 1 1 I | | | | DIMENSI | ON: 3/8' | LENGTH | X 3/4″ WID | .: TH X 1/4″ | | | | | | | 1 I 1 1 1 | · · · • · |
| ÷. | 1 | 1 1 1 1 1 | | | | | | 5: ±0.004″ | | | // 1 1 1 1 | | | 1 1 1 1 1 | : | NORTH | |
| : : | | Q:" | | | | 1 | -γ. | | | - F | - i• (| S. | * | | (? | > ' | |
| | | 일상 | | | | <u>–</u> .:., | | | | | | 24.0 | | | | n. L | 1 1 1 1 1 |
| ÷ | | | :÷. | ·:, | ::. | MA | DUCT II FERIAL: PE: BLC | | 0474 | · · | | | | | :÷. | Ч. | |
| 10 | | | | | : | DIM | ENSION | 1: 3/8″ LI | | | | | THICK , V | WITH ST | EP IN | i. | |
| | | | | | | WEI | | ES: ±0.00): 0.28 2 | | | | | | t. | | | |
| :÷. | · · . | | :1. | ÷., | | ÇOA PUL | ATING: I L FORCI | NICKEL (E(LBS): 1 | 3.01 | | ETS | ··. | ÷. | | · · . | 1. | |
| | | | | 11 | : | MAG | GNETIZA | ELD(GA) ATION D FACE: 3 | IRECTIO | ON: THR | | | NESS | | | | |
| | 1. | ÷., | 1 | PROPRIET | ARY AND CONFI | MAX | | ATING TI | EMP(C/I | =): 80/17 | 6 | : | | | : | : | |