,									1									
	ST	anford	magn	стя				1									- 1 - - -	
		11	<u>11.</u>		11	i.	.1.	11	1a.		11	11.		11	: ::::::::::::::::::::::::::::::::::::			. : .
	÷	ч		÷.,	1		-		<u>_</u>		4			1.1	·	Ą		
		E.	t		;'	<u>, ↓.</u> :			at		E.					1		::
		1 - 1 1 - 1 1 - 1	h.,				ON: 2″ X	3/8″ X 1/3	8" THICK	.1.					:		NORTH	
	÷.,	147	Q:"				1.1	Ť	N. Fr. [		1	₩.	Ś	1		(AR)	2	
				- 	<u>D</u> N			Z/ -			T \		2				<u>_</u>	
	.1.		<b>1</b> 1.		<u> </u>	: ↓	MAT	DUCT II ERIAL: PE: BLC		0580	11	:	, <b>:</b> ,		ii.	.:	141	
						:	DIM	ENȘION						1	;			
		I.					WEI		.): 0.41			Λ ±0.00					$\geq$	
	.1.	1 i i i i	<u>11.</u>			in.	ÇOA PULI	TING: N FORCI	NICKEL C E(LBS): 12	2.36		IETS	: . : .		1	÷.,	a' in	
	÷.,		;···		1	:	MAC	GNETIZA	ELD(GAU ATION D FACE: 2	IREÇTI	ON; THR	OUGH <sup>-</sup>	THIÇKI	IESS	111	•••.	÷	
	÷.,	}		1	PROPRIET	ARY AND CONFIL			TING TE				STANDARD M	AGNETS		1		
		1 1 1 1 1			A + +		1											