	1.1		111	1.1			1.1			тi	τ.		1 1	d.	111		r l	
ľ	ST	anford	magn	ETS	:-:	11		::1										1
С С. 1 С	ter -			ter.			<b>.</b>						`;·			·		
						_φ	DIMENS	ION: 3/8" D	9IA. X 5/8"	THICK								
<u>e</u>		.:'				11		*	( <sup>1</sup> · · ·	<u>1</u>	.:*				114		e <sup>t</sup>	
ľ								i i		$\frac{1}{2}$					1 - 1 - 1 - 1			
	'	.4	1	÷	,4	1	' (r	esi.		'p	.4	1			1	'p		1
a		a'		<u>.</u>	NORTH				H.			99				- 1 - 1 - 1	a'	
E.		1 1 1 1 1			· <b>A</b>		·.:	:			:::							
1	'e		1.	÷.		1	MA	DDUCT II TERIAL: APE: CYL	NDFEB	N0330			ʻ	a <sup>11</sup>	- i  	'.		
		a'	:				DIN	/ENSION LERANCI	I: 3/8″ C			СК 🔛		.e*				
ľ					:-1		WE	IGHT(OZ ADE: N42	.): 0 <mark>.</mark> 3			3.		i:				1
	'÷			<u>'</u> ;·		1	CO PUI	ATING: N LL FORCI	NICKEL E(LBS): 8	3.62		NETS	;		1 1			
er.	÷	af i			:		MA	RFACE FI GNETIZA GNETIC	ATION [	DIRECT	ION: TH	ROUGH	THICK	NESS	111			
r E	· -			1	PROPRIETARY	AND CONFIE		X OPERA								1.1		
ţ.	'P	, C	1		, <sup>1</sup> .		' ( T			'P	x i x i	1			1 I. I.I. I.		K I	