	11		111						111			, , , ,	1	al d	1	a ' i		
	ST	апгояр	magn	ETS		·:		- F 1 - F	':	.::		';		· · ·	ſ.	.::	 	1
	14	- 																1
						/ Ø	DIMENS	ION: 1 1/2	" DIA. X 3/4	4″ THICK								
r i	, · ]	.:*	; · ·	.4					; · ·				, š	.:'	i m		.:'	
1	.41	с. 1. 1.	÷.			·;		- 1 1 1	i.	τ <sup>1</sup> 1	 	5					 	1
	1 1 1			<b>.</b>	- 1 1		 				ļ	4.				1 1 1 1		1 1 1 1
	:		:"	.4	NORTH	/										]		
1	.41		<u>`</u> }		Â	·.	-		5	.11		÷.	.::		`{ }	.::	· · ·	1
1	1÷					4.	MA	TERIAL:		N0226				j.		14		1 1 1 1
	.::	.:*	:			;	DIN					HICK∷ ′		a'	;			
1	.4	r i r	<b>`</b> }	. ::	1 I 1 I	1		IGHT(OZ ADE: N5	Z.): 5,75	r.)	 	1			1	.::	i i C	ł
	5.÷			<u>.</u>	- - -	4.	CO	ATING:	NICKEL E(LBS): ´		ED MAG	NETS		·	Ч.,		·	
		:1	;		e <sup>r</sup>		MA	GNETIZ	TELD(GA ATION [ FACE: <sup>-</sup>	DIRECT	ION: TH	IROUGH	THICK	NESS	111		1 1 1	
:	÷,		1	÷.,	PROPRIETAR	Y AND CONFID	MA	X OPER	ATING T	EMP(C	/F): 80/´	176 PROPERTY OF S			1	i,		
			· ] .															